

ST-100

Downtime on equipment is something none of us want. Having visibility over your equipment's operating status gives you the power to make sound, informed, and timely decisions to optimize your operations. AMCI-Wireless can help by giving you the information you need to make these decisions and minimize or even prevent downtime in your operations. The ST-6100 Satellite Communication Terminal utilizes two-way satellite technology to give you important information and alert you to critical conditions, in many cases giving you the opportunity to respond before failure even occurs.



PRODUCT SPECIFICATIONS

SATALARM® SERVER WEB-BASED SCADA

- Web browser based historian
- Color graphical interface
- User configurable displays
- Customizable dashboard
- Multi data point graphs
- Data tracking
- Integrated maps
- Equipment configuration
- Device control
- Data conditioning
- Reporting

SATELLITE MESSAGING

- Two-way, global, IsatData Pro • From terminal (max per message) - 6400 bytes
- To terminal (max per message) - 10,000 bytes

MODEL OPTIONS

- ST-6100 - side mount or bottom mount
- Class 1 Div 2 available upon request

GPS

- Acquisition Time: 1 second (Hot) 29/30/36 seconds(Cold)
- Accuracy: 2 meters (CEP)
- Sensitivity:
- Acquisition: -148 dBm
- Tracking: -163 dBm

PROGRAMMING

- Reporting (configured over the air): - Configurable time-of-day based schedule - Configurable interval-based schedule - 3 minutes up to once every 3 days - By exception; user definable test conditions
- Modbus-RTU: - 16 configurable commands - Data reportable by schedule, interval, threshold test, any change, or pattern match

MOUNTING KIT OPTIONS

- Pole-mount
- Magnetic-mount

ENVIRONMENTAL

- Operating Temperature: -40°C to +85°C
- Storage Temperature: -40°C to +85°C
- Humidity: 90%RH @ 85°C; meets SAE J1455
- Dust and Water Ingress: IP67
- Vibration - Meets SAE J1455
- Shock (survival): MIL-STD-810G

EXTERNAL INTERFACES

- Serial: 2 ports; RS-232 and RS-485
- I/O: 4 channel; individually configurable as analog input or digital input/output - Analog inputs: 0 – 3.0V, 1.0mV (12-bit) resolution - Digital inputs: -10 – 150VDC safe, pull-up or pull-down - Digital outputs: 32VDC safe, 250mA sinking (open drain), or 3VDC, 25µA (push-pull)
- Additional I/O available using Modbus I/O expansion modules

CERTIFICATIONS/COMPLIANCE

- Satellite - Inmarsat
- Other - CE, FCC, IC, Anatel

POWER

- Input voltage: 9 – 32VDC
- Load dump protection: +150VDC
- Power consumption (typical average @ 12VDC, 22°C):
 - IDP receive: 65mA
 - Receive w/ GPS/Glonass/Beidou: 22mA
 - Transmit: 0.65A
 - Sleep: 100µA

CONTACT DETAILS

CORPORATE

255 Pennbright Drive,
Suite 240
Houston, TX 77090

COLORADO

2171 S Trenton Way,
Suite 217
Denver, CO 80231

AUSTRALIA

2/26 Carbine Way,
Mornington,
Victoria 3931

INDIA

146/1 Bakhtawar RAM
Indore, Madhya Pradesh
PIN 452018

PH: 346 701 5711

PH: 303 279 2002

PH: +61 400
770790

PH: +91
7898144480

PRODUCT SPECIFICATIONS

SATELLITE COMMUNICATION

- Frequency: - Carriage return (CR): 1626.5 – 1660.5 MHz; 1668.0–1675.0 MHz - To terminal: 1518 – 1559 MHz
- Typical Latency: <15 sec, 100 bytes
- Elevation Angle: -5° to 90° for communications link
- Maximum EIRP: <7.0 dBW

INTERNAL BATTERY

- Lithium ion 2,000 mAh
- Discharge temperature range: -20°C to +75°

PHYSICAL

- 5.0 x 5.0 x 1.9 in. (12.6 x 12.6 x 4.9 cm)
- 1.0 lbs. (0.46 kg)

WARRANTY

- 3 year standard limited warranty

CONTACT DETAILS

CORPORATE

255 Pennbright Drive,
Suite 240
Houston, TX 77090

COLORADO

2171 S Trenton Way,
Suite 217
Denver, CO 80231

AUSTRALIA

2/26 Carbine Way,
Mornington,
Victoria 3931

INDIA

146/1 Bakhtawar RAM
Indore, Madhya Pradesh
PIN 452018

PH: 346 701 5711

PH: 303 279 2002

PH: +61 400
770790

PH: +91
7898144480